

M/C 76-Series



Features

- Aluminum alloy body is black anodized for corrosion resistance.
- 1.1" of stroke provides the fluid displacement needed for a wide variety of applications.
- Industry standard 2.25" (center-to-center) front flange mount.
- Dual AN-3 outlet ports.
Top and rear port options allow for greater flexibility with plumbing. Factory installed port plug can be removed so that a bleed fitting, brake pressure sensor or brake light switch could be fitted.
- Top outlet port is compatible with both AN-3 and banjo fittings. Both outlet ports can be used with standard fitting without the need for modification or adapters.
- AN-4 inlet port adapter.
- Weighs .69 lbs (varies by bore size).

76-Series master cylinders share a similar compact body as the Tilton 75-Series, but feature an AN-4 (7/16"-20) inlet port adapter, designed to accept AN-4 fittings when remote-mounted reservoirs are used. Dual outlet ports allow for flexibility for brake line plumbing and enables maximum clearance.

| Bore Size | Part Numbers |
|------------------|---------------|
| 5/8" (15.88mm) | 76-625 |
| 7/10" (17.78mm) | 76-700 |
| 3/4" (19.05mm) | 76-750 |
| 13/16" (20.64mm) | 76-812 |
| 7/8" (22.23mm) | 76-875 |

